

## LREC9801BF-SFP+

PCI Express x8 Single Port SFP+ 10 Gigabit Server Adapter (Intel 82599EN Based)

Single-Port 10 Gigabit SFP+ Ethernet Server Adapters Provide Ultimate Flexibility and Scalability in Virtual and Unified Storage Environments

### Description:

LR-LINK LREC9801BF-SFP+10G Server Adapters with SFP+ connectivity are the most flexible and scalable ethernet adapters to meet the demands of today's data center environments. Data center networks are being pushed to their limits. The escalating deployments of servers with multi-core processors and demanding applications such as High Performance Computing (HPC), database clusters, and video-on-demand are driving the need for 10 Gigabit connections. Customers require flexible and scalable I/O solutions to meet the rigorous requirements of running mission-critical applications in virtualized and unified storage environments.

### Best Choice for Virtualization

The explosive growth in virtualization is leading to an increasing demand for network performance. With more Virtual Machines (VMs) running on each multi-core server, networking traffic is dramatically increased with each VM competing for available I/O bandwidth. LR-LINK LREC9801BF-SFP+ 10G Server Adapters address networking bottlenecks in virtualized environments. These adapters enable network-intensive applications to achieve the performance expected in a virtualized environment. The LR-LINK 10G LREC9801BF-SFP+ server adapter provides the best networking performance available in the industry, whether the physical port is configured in an emulation mode using the virtual switch in the Virtual Machine Monitor (VMM), or is directly assigned to a virtual machine. In the emulation mode, Intel's I/O technology, Virtual Machine Device queues<sup>1</sup> (VMDq) optimizes network performance by offloading data sorting and copying from the software Virtual Switch in the VMM to the Intel Ethernet 82599 10 Gigabit Controller. This configuration is best suited for a large number of VMs running standard



applications that have limited bandwidth and latency requirements.

For mission-critical applications, where dedicated I/O is required for maximum network performance, users can assign a dedicated virtual adapter port to a VM. Using the PCI-SIG SR-IOV capability on an LR-LINK LREC9801BF-SFP+ 10G server adapter provides direct VM connectivity and data protection across VMs. SR-IOV technology allows the data to bypass the software virtual switch and provides near-native performance. It assigns either physical or virtual I/O ports to individual VMs directly. This technology is best suited for applications that demand the highest I/O throughput and lowest latency performance such as database, storage, financial and other applications.

PCI-SIG SR-IOV is a mechanism for devices to advertise their ability to be directly assigned to multiple virtual machines. SR-IOV allows for the partitioning of a PCI function into many virtual interfaces for the purpose of sharing the resources of a PCI Express\* (PCIe) device in a virtual environment. These virtual interfaces are called Virtual Functions. Each virtual function can support a unique and separate data path for I/O-related functions within the PCI Express hierarchy. Use of SR-IOV with a networking device, for example, allows the bandwidth of a single port (function) to be partitioned into smaller slices that may be allocated to specific VMs, or guests, via a standard interface.

## Unified Networking and Storage

The family of LR-LINK LREC9801BF-SFP+ 10G server adapters lowers your data center total cost of ownership (TCO) by providing the ability to route LAN and SAN traffic over a single fabric.

## Support for Fiber Channel over Ethernet (FCoE)

FCoE encapsulates Fiber Channel frames over standard Ethernet networks, enabling Fiber Channel to take advantage of 10GbE networks while preserving its native protocol. The LR-LINK LREC9801BF-SFP+ 10G server adapter offer FCoE hardware acceleration to provide performance comparable to FC HBAs. The server adapters support Data Center Bridging, also known as Converged Enhanced Ethernet (CEE), which allows customers to configure traffic classes and priorities to deliver a lossless Ethernet fabric. An Intel Ethernet X520 server adapter reduces TCO by eliminating redundant fabrics and saves the cost of expensive FC HBAs and FC switch ports.

## Support for iSCSI

The server adapters provide complete support for proven native OS and VMM iSCSI initiators as well as iSCSI boot. Historically, CRC32C computation has degraded system performance, but now with the CRC instruction set included in the latest Intel® Xeon® processors, CRC validation is possible with minimal impact to network throughput while delivering superior data integrity. The LR-LINK LREC9801BF-SFP+ server adapters do it all 10 Gigabit LAN, FCoE, and iSCSI; truly delivering on the promise of unified networking.

## Reliable Performance

The family of LR-LINK LREC9801BF-SFP+ 10G server adapters includes a number of advanced features that allow it to provide industry-leading performance and reliability.

## Security Optimizations

The adapters support IPsec offload for Microsoft's Network Access Protection (NAP), Active Directory,\* and future security capabilities in Windows\* 7. A LR-LINK LREC9801BF-SFP+ 10G server adapter allows customers to run a secure network environment without sacrificing performance.

## PCIe v2.0 (5 GT/s)

PCIe v2.0 (5GT/s) support enables customers to take full advantage of 10GbE by providing a maximum of 20Gbps bi-directional throughput per port on a single dual port card.

## Designed For Multi-core Processors

Support for technologies such as multiple queues, receive-side scaling, multiple MSI-X vectors, and Low Latency Interrupts allow the LR-LINK LREC9801BF-SFP+ 10G server adapter to provide high-performance 10 Gigabit connectivity in multi-core server blades. These technologies distribute network processing across multiple CPU cores, improving overall performance.

## Features

General  
Intel® 82599 10 Gigabit Ethernet Controller SFP+ Connectivity  
Low-profile  
Load balancing on multiple CPUs  
iSCSI remote boot support  
Fibre Channel over Ethernet (FCoE) Support  
Support for most network operating systems (NOS)  
RoHS-compliant2  
Intel® PROSet Utility for Windows\* Device Manager  
Time Sync (IEEE 1588, 802.1as)

## I/O Features for Multi-core Processor Servers

Intel® Direct Cache Access (DCA)  
MSI-X support  
Low Latency Interrupts  
Header Splits and Replication in Receive  
Multiple Queues: 128 Tx and Rx queues per port  
Tx/Rx IP, SCTP, TCP, and UDP checksum offloading (IPv4, IPv6) capabilities  
Tx TCP segmentation offload (IPv4, Ipv6)  
Receive and Transmit Side Scaling for Windows environment and Scalable I/O for Linux\* environments (IPv4, IPv6, TCP/UDP)  
IPsec Offload  
MacSec

## Virtualization Features

VMDq  
Next-Generation VMDq1 (64 queues per port)  
PC-SIG SR-IOV Implementation (64 virtual functions per port)  
Virtual Machine Load Balancing (VLMB)  
Advanced Packet Filtering  
VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags

## Manageability Features

Preboot eXecution Environment (PXE) Support  
Simple Network Management Protocol (SNMP) and Remote Network Monitoring (RMON) Statistic Counters  
iSCSI Boot  
Watchdog Timer



## Adapter Product Features

Intel® PROSet Utility  
Plug and play specification support  
Receive Side Scaling  
Direct Cache Access (DCA)

## Advanced Software Feature

Adapter fault tolerance (AFT)  
Switch fault tolerance (SFT)  
Adaptive load balancing (ALB)  
Teaming support  
IEEE 802.3ad (link aggregation control protocol)  
PCIe Hot Plug\*/Active Periphena Component  
Interconnect (PCI)  
IEEE 802.1Q\* VLANs  
IEEE 802.3 2005\* flow control support  
Tx/Rx IP, TCP, & UDP checksum offloading (IPv4, IPv6) capabilities (Transmission control protocol(TCP), user datagram protocol (UDP), Internet protocol (IP)  
IEEE 802.1p\*  
TCP segmentation large send offload  
MSI-X supports Multiple Independent Queues  
Interrupt moderation  
IPv6 offloading — Checksum and segmentation capability extended to new standard packet type

## Network Operating Systems (NOS) Software

Support  
Windows 7 32-bit (64-bit)  
Windows 8 32-bit (64-bit)  
Windows 8.1 32-bit (64-bit)  
Windows 10 32-bit (64-bit)  
Windows Server 2003 32-bit (64-bit)  
Windows Server 2008 32-bit (64-bit)  
Windows Server 2008 R2 32-bit (64-bit)  
Windows Server 2012 32-bit (64-bit)  
Windows Server 2012 R2 32-bit (64-bit)  
Linux kernel 2.6.30 or greater (x86\_64) (w/ SR-IOV support)  
FreeBSD 7.2 or later  
Linux RHEL 5.6  
Linux RHEL 6.x  
Linux SLES 11 Sp1  
Linux SLES 10 Sp4  
OS Independent  
DOS NDIS 2  
DOS ODI  
EFI 1.1  
UEFI 2.1  
Vmware ESX 4.02  
Vmware ESX 4.02  
VMware Workstation

## Order Information:

M/N	Description
LREC9801BF-SFP+	PCI Express x8 Single Port SFP+ 10 Gigabit Server Adapter (Intel 82599EN Based)

PS: The above details are only for reference, if there is any change, no inform will have



## ORDER CODES

LREC9801BF-SFP+

## COMPANION PRODUCTS

LR-LINK PCI 100FX Desktop Adapter  
LR-LINK PCIe 100FX Desktop Adapter  
LR-LINK PCI 1000BASE-SX/LX Desktop Adapter  
LR-LINK PCIe 1000BASE-SX/LX Desktop Adapter  
LR-LINK PCIe 1000BASE-SX/LX Server Adapter  
LR-LINK PCIe 10GBASE-SR/LR Server Adapter  
opper NIC  
LR-LINK ®PCI 10/100Mbps Desktop Adapter  
LR-LINK ®PCIe 10/100Mbps Desktop Adapter  
LR-LINK ®PCI 10/100/1000Mbps Desktop Adapter  
LR-LINK ®PCIe 10/100/1000Mbps Desktop Adapter  
LR-LINK ®PCIe 10/100/1000Mbps Server Adapter  
LR-LINK ®PCIe 100/1Gbps/10Gbps Server Adapter

## ONLINE DOCUMENTS

For the latest product information, visit us Web  
at <http://www.lr-link.com/>

## DRIVERS AND PRODUCT LIST

To get the latest product list and drivers, please  
visit us at [http://www.lr-link.com/ProductDriver/  
index1.shtml](http://www.lr-link.com/ProductDriver/index1.shtml)

## FOR PRODUCT INFORMATION

To know the network card basic knowledge to  
choose the suitable card you need, please visit  
us at <http://www.lr-link.com/product.html>  
To get the product datasheet, please contact the  
sales in Shenzhen Lianrui Electronics CO.,LTD.

## CUSTOMER SUPPORT

LR-LINK customer Support Services offers a broad  
selection of programs including phone support and  
warranty service. For more information, contact us at  
<http://www.lr-link.com/service.shtml> Service and  
availability.

**LR-LINK**®  
Link your world to everywhere

Professional supplier of NIC

LianRui Electronic Co.LTD

A professional supplier of high-quality NIC: PCI,PCI-X,PCI-E;SC,ST,LC,SFP,SFP+;  
100M,1G,10G;single,dual,quad ports.all series fiber and copper NIC with nearly 100  
specifications which can meet demands of various applications, continuously creates  
value for customers and partners as well as OEM/ODM services provided.

Shenzhen Lianrui Electronics CO.,LTD

ADD:C4 Bldg., Xintang Industry Zone, Baishixia Fuyong Town, Bao'an District  
Shenzhen China 518103

[www.lr-link.com](http://www.lr-link.com)

Tel:86-755-33671531 Fax: 86-755-29082065

Product sales: [lrlink@lr-link.com](mailto:lrlink@lr-link.com)

Technical Support: [support@lr-link.com](mailto:support@lr-link.com)

OEM & ODM service: [info@lr-link.com](mailto:info@lr-link.com)

Copyright © Shenzhen Lianrui Electronics CO.,LTD, 2004-2013.  
All rights reserved.